


Crossmax SLR



**Rims:**

- Colour: double anodization, black rim, silver ISM
- Disc brake specific profile: no braking surface
- Drilling: Fore
- ISM 3D
- Joint: SLIP
- Material: Maxtal
- Valve hole diameter: 6.5 mm

**Spokes:**

- Colour: black
- Count: 24 front and rear
- Lacing: front crossed 2, rear Isopulse
- Material: Zicral
- Nipples: integrated M7 aluminium with brake rings

**Hubs:**

- Bearings: QRM+
- Colour: red
- Free wheel mechanism: FTS-X, steel
- Front and rear bodies: oversize aluminium
- Front axle: aluminium
- Rear axle size: 9 x 135
- Rear axle: titanium and aluminium

**Compatibility:**

- Disc brakes: International Standard, Center-Lock
- ETRTO size: 559x17c
- HG 8/9-speed
- Recommended tyre sizes: L0 to 2.1
- Tyre: UST Tubeless and tube type


**MRRP RM 3700**

Crossmax SLR 09 features a patented Mavic technology used for the first time : ISM 3D. Inter Spoke Milling 3D pushes the concept one step further by machining not only the lower bridge of the rim but also its sidewalls. The result is a lighter rim providing the most dynamic ride ever : instant acceleration, direct steering and reactive braking. The front wheel is also available in 20x110 version, providing better bike handling, thanks to a stiffer front end. Also available in lefty version.

• Weight: 1420 grams per pair  
• Front wheel: 600 grams  
• Rear wheel: 820 grams

**CENTER LOCK**  
**CROSSMAXX SLR WHEEL SET**

Done



100% Crossmax\_SLR\_4bb73005ca0c7.jpg

Rating: Not Rated Yet  
[Ask a question about this product](#)

Manufacturer: [Mavic](#)