

Crossmax SLR




- Rims:**
- Colour: double anodization, black rim, silver ISM
 - Disc brake specific profile: no braking surface
 - Drilling: Forc
 - ISM 3D
 - Joint: SLP
 - Material: Maxtal
 - Valve hole diameter: 6.5 mm
- Spokes:**
- Colour: black
 - Count: 24 front and rear
 - Lacing: front crossed 2, rear Isopulse
 - Material: Zicral
 - Nipples: integrated M7 aluminium with brake rings
- Hubs:**
- Bearings: QRM+
 - Colour: red
 - Free wheel mechanism: FTS-X, steel
 - Front and rear bodies: oversize aluminium
 - Front axle: aluminium
 - Rear axle size: 9 x 135
 - Rear axle: titanium and aluminium
- Compatibility:**
- Disc brakes: International Standard, Center-Lock
 - ETRTO size: 55/93/17c
 - HG 8/9-speed
 - Recommended tyre sizes: 1.0 to 2.1
 - Tyre: UST Tubeless and tube type

MRRP RM 3700

Crossmax SLR 09 features a patented Mavic technology used for the first time: ISM 3D. Inter Spoke Milling 3D pushes the concept one step further by machining not only the lower bridge of the rim but also its sidewalls. The result is a lighter rim providing the most dynamic ride ever: instant acceleration, direct steering and reactive braking. The front wheel is also available in 20x110 version, providing better bike handling, thanks to a stiffer front end. Also available in lefty version.

- Weight: 1420 grams per pair
- Front wheel: 600 grams
- Rear wheel: 820 grams

CENTER LOCK
CROSSMAXX SLR WHEEL SET

Done  100% Crossmax_SLR_4bb73005ca0c7.jpg

Rating: Not Rated Yet
[Ask a question about this product](#)

Manufacturer: [Mavic](#)